



# MATERIAL SAFETY DATA SHEET EP 1115 Clear Part B

03/06/2008

W186 N11687 MORSE DRIVE GERMANTOWN, WI 53022  
262-502-6610 FAX 262-502-4743

CHEMTREC EMERGENCY PHONE 1-800-424-9300

REVISION DATE: 03/06/2008

## SECTION I - IDENTIFICATION

PRODUCT NAME: EP 1115 CLEAR PART B  
CHEMICAL COMPOSITION: MIXTURE  
CHEMICAL FAMILY: POLYAMINE BLEND

### HMIS RATINGS

HEALTH= 2      FLAMMABILITY= 1      REACTIVITY= 0      PERSONAL PROTECTION = B  
0=LEAST 1=SLIGHT 2=MODERATE 3=HIGH 4=EXTREME B=GLOVES, SAFETY GLASSES

## SECTION II - HAZARDOUS INGREDIENTS

| NAME                                    | CAS #      | OSHA PEL | ACIGH TLV |
|---|------------|----------|-----------|
| POLYMERCAPTAN RESIN*                    | NA         | NA       | NA        |
| POLYAMIDE RESIN                         | 68082-29-1 | NA       | NE        |
| 2,4,6-TRIS((DIMETHYLAMINO)METHYL)PHENOL | 90-72-2    | 5 ppm    | 5 ppm     |

\* EXACT IDENTITY WITHHELD AS A TRADE SECRET

## SECTION III - PHYSICAL DATA

FLASH POINT (PMCC): >200°F      BOILING POINT: >200°F      VAPOR DENSITY: > AIR  
EVAPORATION RATE: NIL      % VOLATILE BY VOL.: 0      SPECIFIC GRAVITY: 1.05  
SOLUBILITY IN WATER: PARTIAL      VAPOR PRESSURE: < 1mm Hg  
APPEARANCE AND ODOR: AMBER LIQUID, MILD AMINE ODOR

## SECTION IV - FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA: Water fog, carbon dioxide, foam or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.

UNUSUAL FIRE & EXPLOSION HAZARDS: Keep containers tightly closed. Water may be used to cool unruptured containers.

## SECTION V - REACTIVITY

STABILITY: STABLE



# MATERIAL SAFETY DATA SHEET EP 1115 Clear Part B

03/06/2008

---

W186 N11687 MORSE DRIVE GERMANTOWN, WI 53022  
262-502-6610 FAX 262-502-4743

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: High temperatures, high humidity.

MATERIALS TO AVOID: STRONG OXIDIZING AGENTS, ACIDS, EPOXY RESINS IN UNCONTROLLED CONDITIONS

---

## SECTION VI - HEALTH HAZARD DATA

---

### EFFECTS OF OVEREXPOSURE:

ACUTE: SKIN; Primarily redness and irritation.

CHRONIC: May cause skin sensitization.

ACUTE: INHALATION; Symptoms may include burning sensation, coughing and shortness of breath.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Chronic diseases of the skin,

PRIMARY ROUTES OF EXPOSURE: DERMAL

EMERGENCY FIRST AID PROCEDURES: Move person to fresh air. Restore breathing. Treat symptomatically. Consult a physician.

EYES: Flush eyes with water for at least 15 minutes. Take to a physician for medical treatment.

SKIN: Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists.

INGESTION: Drink one or two glasses of milk or water. Do not induce vomiting. Give medical attention immediately.

Never give anything by mouth to an unconscious person.

---

## SECTION VII - PROTECTIVE MEASURES

---

RESPIRATORY PROTECTION: Avoid breathing vapors/mists. Use approved chemical/mechanical filters designed to remove a combination of particulates and organic vapors in open and restricted areas when ventilation does not meet the requirements of 29 CFR 1910.134. Use approved airline type respirators or hoods in confined areas.

VENTILATION: Sufficient ventilation in pattern and volume to keep the air contaminant concentration below applicable exposure limits. All application areas should be ventilated in accordance with OSHA regulation 29 CFR 1910.134

PROTECTIVE GLOVES: Use neoprene or other impervious gloves to prevent skin contact.

EYE PROTECTION: Use safety glasses with side shields as minimum protection.

OTHER PROTECTIVE EQUIPMENT: Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

HYGIENIC PRACTICES: Wash hands before eating, smoking or using toilet facilities. Do not smoke in any chemical handling and storage area. Food or beverages should not be consumed anywhere near this product is handled or stored.



**MATERIAL SAFETY  
DATA SHEET  
EP 1115 Clear  
Part B**

03/06/2008

---

W186 N11687 MORSE DRIVE GERMANTOWN, WI 53022  
262-502-6610 FAX 262-502-4743

---

---

**SECTION VIII - SPILL OR LEAK PROCEDURES**

---

SPILLS: Contain and remove with absorbent material. Avoid contact.

WASTE DISPOSAL METHOD: Disposal should be done in accordance with Federal (40 CFR Part 261), State and local regulations. Before attempting clean-up, refer to hazard caution information in other sections of the MSDS form. Use only licensed hazardous waste disposal companies.

---

**SECTION IX - SPECIAL PRECAUTIONS**

---

HANDLING AND STORAGE: Do not store near heat or open flame.

OTHER: Empty container should not be reused.

---

**SECTION X - TRANSPORTATION INFORMATION**

---

DOT PROPER SHIPPING NAME: NOT REGULATED  
HAZARD CLASS OR DIVISION: NA  
PACKING GROUP NUMBER: NA  
REQUIRED LABEL: NONE  
UN NUMBER: NA

TSCA STATUS: All components of this product are listed on, or exempted from the requirement to be listed on, the TSCA Inventory.

PROPOSITION 65 SUBSTANCES (component(s) known to the State of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986"): None

---

The information contained herein is based upon data taken in good faith and considered accurate. However, no warrant is implied or expressed regarding the accuracy of this data or the results obtained from the use thereof.

NA= Not Available na= not applicable NE=Not Established ND=Not Determined mppcf=million parts/ft3  
mg/m3= milligrams per cubic meter